



SLEEPER LAYER SL600 HD

Designed for high output sleeper laying.

Up to six adjacent sleepers can be laid simultaneously from an accompanying supply. Lifted into position, their correct placement is ensured by a precision gauging system that spreads the sleepers to the desired distance.

- The telescopic frame structure make it small and safe to operate.
- No risk of pointing out on the adjacent track when grabbing sleepers from a rail car.
- As an option the unit can be equipped with a safety lifting function to prevent the operator from dropping sleepers.
- Easy adjustable, fit most type of sleepers.

The Sleeper Layer SL600 can be delivered with our without tilt rotating function.

NETWORK RAIL PRODUCT ACCEPTANCE NO: PA05/03134



Innovation House, 3 Western Wood Way, Langage Science Park
Plymouth, PL7 5BG, Devon, UNITED KINGDOM
Email: sales@vortok.co.uk Website: www.vortok.co.uk
Phone: +44 (0) 1752 349200 Fax: +44 (0) 1752 338855

SPECIFICATIONS

Weight	1309 kg (2885 lb)
Length min	2000 mm (78.7 in)
Length max	4475 mm (176.2 in)
Height	1333 mm
Max distance between sleepers	762 mm (30 in)
Item number	5000-641

*Please note that the unit pictured above could be equipped beyond standard.
This brochure is subject to change without notice.*

