



## SLEEPER LAYER SL800

Designed for high output sleeper laying.

Up to eight adjacent sleepers can be laid simultaneously from an accompanying supply. Lifted into position, their correct placement is ensured by a precision gauging system that spreads the sleepers to the desired distance.

- The telescopic frame structure make it small and safe to operate
- No risk of pointing out on the adjacent track when grabbing sleepers from a rail car.
- As an option the unit can be equipped with a safety lifting device to prevent the operator from dropping sleepers.
- Easy adjustable, fit most type of sleepers.

The Sleeper Layer SL800 can be delivered with or without tilt rotating function.

### SPECIFICATIONS

Weight	(including bracket)	2410 kg (5313 lb)
	(excluding bracket)	2060 kg (4541.5 lb)
Width		2578 mm (101.5 in)
Length min		3005 mm (118.3 in)
Length max		5985 mm (235.6 in)
Height		1660 mm (65.4 in)
Item number		1035-0001

*Please note that the unit pictured above could be equipped beyond standard.  
This brochure is subject to change without notice.*

NETWORK RAIL PRODUCT ACCEPTANCE NO: PA05/03134



Innovation House, 3 Western Wood Way, Langage Science Park  
Plymouth, PL7 5BG, Devon, UNITED KINGDOM  
Email: sales@vortok.co.uk Website: www.vortok.co.uk  
Phone: +44 (0) 1752 349200 Fax: +44 (0) 1752 338855

